

# Ji03 Portable GPS Tracker



- ▶ GPS+LBS+A-GPS fast positioning
- 🔋 1200mAh battery
- 📞 SOS alarm & family numbers
- 📞 Calling receive function
- 📡 Voice monitor
- 📱 Vibration detect
- 📍 Geo-fence



Hardware Specification	
GSM Specification	
Communication model	GSM
GSM frequency	850/900/1800/1900MHz
GPRS	Class 12,TCP/IP
Memory	64MB
Phrase error	RMSPE<5,PPE<20
Max. output	GSM850/GSM900:33±3db GSM1800/GSM1900:30±3db
Max. frequency error	±0.1ppm
Sensitivity	Class II RBER2%(-10dBm)
GPS Specification	
GPS chip	MTK high sensitivity GPS chip
Frequency	L1,1575.42MHz C/A code
Channels	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
Positioning time	Hot-start:≤2 sec(open sky)
	Cold-start:≤35 sec(open sky)

Main Specification	
Monitoring scope	≤5 meters
Button	2 Speed dial button,1 SOS button,1 MODE button,1 Power switch button
GSM/GPS antenna	Built-in
LED indicator light	GPS(blue),GSM(green), Power(red)
Battery	120mAh/3.7V lithium-polymer battery
Voltage/Current	3.7VDC/50mA
Standby time	10 Days(Deep sleep mode)
Work time	15 hours(GPS normally open mode)
Talk time	5.5 hours
Charger	5VDC/1A
Color	Blue and white
Dimensions	73.0(L)×45.0(W)×16.0(H)mm
Weight	54g
Operating temperature	-20°C~+60°C