

Ji06 GPS Kid's Phone



-  GPS+LBS+A-GPS fast locating
-  Voice monitor
-  SOS button
-  Family numbers
-  Calling controlled
-  Geo-fence



Hardware Specification	
Main Specification	
Monitoring scope	≤5M
Colored monitor	Resolution 128×128 pixels
Keypad indicator	4 family keys, 2 function keys,
	1 SOS key, 1 battery keys
GSM/GPS antenna	Built-in
Battery	600mAh/3.7V lithium-polymer battery
Voltage/Current	3.7VDC/80mA
Standby Time	120 hours (LBS 10 minutes to report)
Call time	4 hours
Charging voltage	5V DC
Color	Pink(HAPPY BEAR), Blue(MUSIC BEAR)
	Champagne(DOUBLE BEAR)
Dimensions	65.0(L)×44.5(W)×18.0(H)mm
Weight	52g
Operating temperature	-20°C~+60°C

GSM Specification	
Communication system	GSM
GSM spectrum	850/900/1800/1900MHz
GPRS	Class 12, TCP/IP
	64 MB
Phrase error	RMSPE<5, PPE<20
Max output	GSM850/GSM900: 33±3db
	GSM1800/GSM1900: 30±3db
Max frequency error	±0.1ppm
Sensitivity	Class II RBER2%(-10dBm)
GPS Specification	
GPS chip	uBlox high sensitivity chip
Frequency	L1, 1575.42MHz C/A code
Channels	56
Location accuracy	<10 meters
Tracking sensitivity	-162dBm
Acquisition sensitivity	-148dBm
Positioning time	Hot-start: ≤2 sec(open sky)
	Cold-start: ≤35 sec(open sky)